

CCSE-CML CCS700 Conference Chairman unit

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Priority button for chairman microphone.
- ▶ Optional chime tone facility preceding chairman announcements.
- ▶ Modern, unobtrusive styling to match the CCSE-DL Delegate Units.
- ▶ Microphone with flexible stem and light ring.
- ▶ Two headphone sockets.

The CCS700 Ultra Discussion System is a suitable for use in meetings and conference venues with a limited number of participants.

The CCSE-CML Chairman Units are equipped with enhanced functionality that enables the user to take the role of chairman in a conference or meeting. The unit has a fixed microphone with flexible stem. Headphone sockets can be used to listen to the discussion in situations with excessive background noise.

System overview

Priority button for chairman microphone

In addition to the 'microphone on' button the chairman units feature a 'chairman priority' button. When pressed the priority button causes all currently active delegate microphones to be permanently muted.

Optional chime tone facility for preceding chairman announcements

A sliding switch is available on the rear of CCSE-CU which can be used to activate the chime tone to precede chairman priority calls.

Built-in loudspeaker

Loudspeaker volume is set centrally at the Control Unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

Two headphone sockets

Two 3.5 mm (0.14 in) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit.

Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

Controls and Indicators

- Microphone on/off button.
- Chairman priority button.
- Rotary volume control for adjusting headphone volume.
- Loudspeaker, automatically muted when microphone is on.
- Microphone 'on' indicator (red LED).
- Light ring indicator on microphone stem, lights up red when microphone is on.

Interconnections

- 1 x 2.7 m (106.3 in) cable terminated with a 8-pin male connector for loop-through connection to other.
- 1 x 8-pin circular female connector for loop-through connection to other delegate or chairman units.
- 2 x 3.5 mm (0.14 in) stereo headphone sockets.

Parts included

Quantity	Components
1	CCSE-CML CCS700 Conference Chairman unit

Technical specifications**Electrical**

Nominal Acoustic Input	85dB SPL
Frequency Response	400Hz to 10kHz

Mechanical

Dimensions (without microphone) (H x W x D)	54x136x138mm
Length of the microphone from the base of the stem	488mm
Weight	1.2 kg
Mounting	Tabletop
Color	Charcoal

Environmental

Operating temperature	-5°C to +45°C
Storage temperature	-40°C to +70°C

Ordering information**CCSE-CML CCS700 Conference Chairman unit**Order number **CCSE-CML****Represented by:****Americas:**

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com